



Gauge on left shown with optional bumpers and handle, gauge on right shown in standard benchmount cabinet with rubber feet.

3 Popular Ranges

- 0.01 to 50 Torr Pirani Gauges
- 1 to 1500 Torr Diaphragm
- 30 Inches Hg to 150 PSIG

Standard Features

- NW-16, 1/8" NPT or Conflat® Flanges
- Bright, Easy to Read Green LED Display
- Bench Mount Cabinet with Rubber Feet
- Bracket Included For 1/8 DIN Panel Mount

BUY NOW! Go to www.vacuumresearch.com to order online

.01 to 50 Torr Digital Pirani Gauge

Benchmount cabinet with rubber feet. Clip for mounting in 1/8 DIN panel cutout included. Sensor cable 10 ft (3m) long. Gauge operates from 15 to 24 VDC, less than 200 mA. An external wall mount supply is included with each instrument. 90 to 240V. 50/60 Hz input and 15 VDC output.

3.5" Wide X 7.4" F to B X 1.84" H.
190 mm W X 188 mm F-B X 46 mm H.
Sensor not included.

P/N: 902142\$592

Sensor, 1/8" NPT, all wetted parts stainless steel.
P/N: 912011\$123

Sensor NW-16, all wetted parts stainless steel.
P/N: 912072.....\$151.Sensor 1.33" OD Conflat®, non-rotatable, all wetted parts stainless steel.
P/N: 912073.....\$177

Sensor VCR-4 FEM, all wetted parts stainless steel. P/N: 912074.....\$227

1 to 1500 Torr Digital Diaphragm Gauge

Benchmount cabinet with rubber feet. Clip for mounting in 1/8 DIN panel cutout included. Sensor cable 10 ft (3m) long. Gauge operates from 15 to 24 VDC, less than 200 mA. An external wall mount supply is included with each instrument. 90 to 240V. 50/60 Hz input and 15 VDC output.

3.5" Wide X 7.4" F to B X 1.84" H.
90 mm W X 188 mm F-B X 46 mm H.

Sensor not included.
P/N: 902143.....\$623

Sensor 1/8" NPT, Silicon Diaphragm
P/N: 912091\$354

Sensor NW-16, Silicon Diaphragm
P/N: 912023.....\$408

Sensor with 1.33" OD Conflat® flange, non-rotatable, and Silicon Diaphragm.
P/N: 912026.....\$408

Sensor with Stainless Steel Diaphragm
1/4" NPT P/N: 912022.....\$561

See page 11 for more flange options.

30 Inches Hg to 150 PSIG Digital Diaphragm Gauge

Benchmount cabinet with rubber feet. Clip for mounting in 1/8 DIN panel cutout included. Sensor cable 10 ft (3m) long. Gauge operates from 15 to 24 VDC, less than 200 mA. An external wallmount supply is included with each instrument. 90 to 240V. 50/60 Hz input and 15 VDC output.

3.5" Wide X 7.4" F to B X 1.84" H.
90 mm W X 188 mm F-B X 46 mm H.
Sensor not included.

P/N: 902144\$674

Sensor 1/8" NPT, Silicon
Diaphragm P/N: 912149\$354

All Stainless Steel Gauge Tubes For Outdoor Applications or Wherever The Use Of 304 SS Is Appropriate. All wetted parts as well as all external parts and connector pins are 304 SS. 1/8 in. NPT, NW-16, Conflat®, VCR-4 and special flanges can be provided. Add "SS" suffix to any tube P/N and to standard tube price:..... add \$61



3 & 5 Position Vacuum Gauges

Ordering Information

Vacuum gauge & switch built into a 1/4 DIN enclosure suitable for bench or panel mounting. Standard sensor cables are each 10 ft. long. Cables up to 500 feet are available.

.01 to 50 Torr, 5 Position P/N: 902255\$954
.01 to 50 Torr, 3 Position P/N: 902267\$879

1 to 1500 Torr, 5 Position P/N: 902256\$986
1 to 1500 Torr, 3 Position P/N: 902268\$986

30" Hg to 150 PSIG, 5 Pos. P/N: 902257 ...\$1,101
30" Hg to 150 PSIG, 3 Pos. P/N: 902269 \$1,025

Urethane bumpers, pair,
P/N: V805001\$65

Carry handle installed on instrument,
P/N: V805005\$30

Power Supply for all 3 Ranges

100 to 240 V, 50-60 Hz input, 15 VDC @ 1.0 A output. Wallmount style with adapter plugs for US, UK, Europe, Australia. P/N: V104124\$79

Power Supplies for instruments shipped in 2005 and before.

115 V 50/60 Hz input, 12 VAC @ 800 mA output. P/N: V104098.....\$21

220 V 50/60 Hz input, 12 VAC @ 800 mA output. P/N: V104123.....\$105