



Panel Mount Indicator on left
1/4 DIN Dual Set Point Controller
on right.



Inset photo shows Bench Mount
Cabinet with optional carry
handle and 3 position gauge
tube selector switch.

- **Reliable T/C Gauge 1 to 1000 mTorr (Microns)**
- **Indicator Only or Indicator with 2 Set Points**
- **Stainless Tubes & Special Flanges Available**
- **Stem and Flanges 300 Series Stainless Steel**
- **Operates With Power From 90 to 240 V, 50/60 Hz**
- **0 to 5 Volt Output For Computer I/O or Control**
- **Fits Same Cutout As Hastings, Televac & Varian**
- **Use With VRC-6 or Hastings DV-6 Gauge Tubes**

Vacuum Research's thermocouple vacuum gauge is a simple and low cost instrument for vacuum measurement in the popular 1 to 1000 mTorr range (microns). It operates with any line voltage from 90 to 240V at 50 or 60 Hz, and can be used with our VRC-6 or Hastings DV-6 gauge tubes. A 0 to 5 VDC analog output is standard on both the indicator and dual set point controller models.

Ordering Information

BUY NOW! Go to www.vacuumresearch.com to order online

Dual Set Point Controller

Thermocouple gauge, 1 to 1000 mTorr range with 0 to 5 VDC analog output plus 2 adjustable set points each with its own SPDT relay contacts rated 3 Amps up to 220 VAC non-inductive. Operates from any line power between 90 and 240 volts, 50 or 60 Hz. 1/4 DIN enclosure with panel mounting jack screws included. Gauge tube not included.

P/N 902109\$684

Indicator; 1 to 1000 mTorr Meter

Thermocouple gauge, 1 to 1000 mTorr range with 0 to 5 VDC analog output, operates with any line power between 90 and 240 volts, 50 or 60 Hz. Gauge tube not included. See drawing on page 40 for dimensions. P/N 902111\$347

Bench Mount Stand with Carrying Handle

5.3 in. wide X 4 in. F to B X 4.7 in. High (6.7 in. handle extended)
(134 X 100 X 120 mm) P/N: 902112.....\$77

3 Position Thermocouple Gauge Indicator; 1 to 1000 mTorr Meter

Includes 3 cables 10 ft. (3 m) long and 3 connectors, bench mount stand and carry handle, gauge tubes not included. Cable length up to 500 ft; (60 m) available. P/N: 902113\$533

5 position Thermocouple Gauge Indicator 1 to 1000 mTorr Similar to above 3 position indicator P/N 902181\$626

Standard T/C Gauge Tubes Interchangeable with Teledyne-Hastings DV-6M & DV-6R. All parts in contact with the process are stainless steel: cup, stem, and flange. The connector pins are nickel plated Kovar.

VRC-6M 1/8" NPT Stainless Steel Body, P/N: 912086\$82

VRC-6M 1/4" SAE 45° Flare, Male S.S. Body, P/N: 912302\$145

VRC-6M NW-16 Stainless Steel Body, P/N: 912096\$145

VRC-6M NW-25 Stainless Steel Body, P/N: 912203\$145

VRC-6M VCR-4 FEM Stainless Steel Body, P/N: 912082\$167

VRC-6M 1.33" Conflat® Stainless Steel Body, P/N: 912083\$145

VRC-6M 1/2" OD Smooth Flange SS Body, P/N: 912085\$82

VRC-6M 2.75 Conflat® Stainless Steel Body, P/N: 912178\$210

VRC-6M VCR-8 FEM Stainless Steel Body, P/N: 912079\$173

Thermocouple Gauge Tubes with Stainless Steel Connector Pins

For outdoor use or applications that require frequent unplugging of the gauge tube connector. All parts are stainless steel: cup, stem, flange, and connector pins.

VRC-6R 1/8" NPT Stainless Steel Pins & Body, P/N: 912087\$149

VRC-6R 1/4" SAE 45° Flare, Male S.S. Body, P/N: 912302SS\$206

VRC-6R NW-16 Stainless Steel Pins & Body, P/N: 912098\$206

VRC-6R VCR-4 FEM Stainless Steel Pins & Body, P/N: 91209\$230

VRC-6R 1.33" Conflat® S.S. Pins & Body, P/N: 912084\$206

VRC-6R 2.75 Conflat® Stainless Steel Pins & Body, P/N: 912213\$230

Thermocouple Gauge Tubes

The VRC-6M and 6R are direct plug-in replacements for the Teledyne-Hastings DV-6M and DV-6R gauge tubes. No adjustment to your instrument is required; just plug them in. These T/C gauge tubes are tested to 1200 PSIG for operation up to 300 PSIG without damage. There is no fragile plastic header, and no easy-to-break plastic key. The result of 30 years of vacuum gauge experience, all tubes have stainless steel bodies with heavy plated metal key and connector pins. For outdoor applications select our 'R' version which has stainless steel connector pins as well as our standard all stainless steel body.

Specifications

Pressure Range: 1 to 1000 milliTorr (1 to 1000 Microns). Air/N₂

Accuracy: Better than ± 1 mTorr from 1 to 20 mTorr. Better than 5% from 20 to 1000 mTorr.

Response Time: 1 mTorr up to atmosphere: less than 1 sec.

Analog Output: 0 to 5 VDC into 10 K ohms minimum.

Gauge Tube: Gauge tubes available with 1/8 inch NPT, NW-16, VCR-4, 1.33 O.D. Conflat® flanges and all stainless steel bodies. This instrument also operates with Hastings DV-6 thermocouple gauge tubes.

Bakeout Temperature: 100 °C (212 °F) in air or vacuum.

Operating Temperature: 4 to 60 °C (39 to 140 °F).

Temperature Coefficient: $\pm$ (1% of reading +0.2 mTorr)/C°.

Power: Any voltage from 90 to 240 V, 50 / 60 Hz under 2 watts.

Line Regulation: Reading changes less than $\pm 0.3\%$ for line voltage change from 90 to 240 Volts.

Relays on Controller Model: Separate relays for each set point. Form C, SPDT, contacts rated 3 amps non-inductive at voltages up to 250 VAC.

Mounting

Indicator Dimensions: See page 40.

Controller: 1/4 DIN panel mount is std. Jack screws included.

Cables: 10 ft. (3 m) cable with connector and 6 ft. line cord provided. Extension cables up to 200 ft. (60 m) available.

Net Weight: Indicator: 0.5 lbs. (0.2 kg); Controller: 1.4 lbs. (0.6 kg).

Ship Weight: Indicator: 2 lbs. (0.9 kg); Controller: 3 lb. (1.4 kg).